

Standard Inverter

AX

Air Sleep Feel
Frost Wash*
STAINLESS PRE FILTER
VECTOR DC INVERTER



RAS-AX10CJT/ AX13CJT



RAS-AX18CJT



RAS-AX10CJT/AX13CJT/AX18CJT

Specification

Model	Indoor	RAS-AX10CJT	RAS-AX13CJT	RAS-AX18CJT	
	Outdoor	RAC-AX10CJT	RAC-AX13CJT	RAC-AX18CJT	
Phase, Voltage, Frequency	φ, Hz	1φ, 50Hz, 220-230V			
Cooling Capacity	kW	2.7 (0.9-3.4)	3.5 (0.9-4.2)	5.0 (0.9-5.8)	
	BTU/h	9,220 (3,070-11,500)	11,942 (3,070-14,330)	17,060 (3,070-19,791)	
SEER	BTU/h · W	18.53	18.66	21.00	
Total Input	W	900 (210-1,190)	1,200 (350-1,350)	1,470 (320-2,000)	
Total Amperes	A	4.8-4.6	5.74-5.49	6.75-6.45	
Air flow (Powerful/H/M/L/Silent)	m ³ /min	10.5/8.5/7.0/5.0/3.0	12.0/11.0/9.5/7.5/3.5	15.0/14.5/12.0/8.0/6.0	
Indoor Sound Level (Powerful/H/M/L/Silent)	dB	44/41/32/24/19	48/43/33/27/19	49/48/40/33/30	
Dehumidifying Capacity	l/h	1.4	1.6	3.4	
Maximum Length/Height of Piping	m	20/10	20/10	20/10	
Diameter for Gas/Liquid	mm	9.52/6.35	9.52/6.35	12.7/6.35	
Power Supply		Indoor	Indoor	Indoor	
Net Dimensions	Indoor (W × H × D)	mm	790x300x230	790x300x230	900x300x230
	Outdoor (W × H × D)	mm	700x468x258	700x468x258	850x650x298
Net Weight	Indoor/Outdoor	kg	10.5/26	9.7/24.5	10.5/43
Refrigerant		R32			

- 1 ON Button / Refresh Mode
- 2 Air Sleep Feel Mode
- 3 Silent / Dry Selector
- 4 Frost Wash Button
- 5 Off Button
- 6 Powerful Mode
- 7 Fan Speed Selector
- 8 Set Temperature Selector
- 9 Off Timer Button
- 10 Up / Down Air Flow Control
- 11 Left / Right Air Flow Control

Outdoor



RAC-AX10CJT/AX13CJT



RAC-AX18CJT