

# Premium Inverter



## Scene Camera Series



RAS-VX13CJT



RAS-VX18CJT / RAS-VX24CJT

## Specification

Model	Indoor		RAS-VX13CJT	RAS-VX18CJT	RAS-VX24CJT
	Outdoor		RAC-VX13CJT	RAC-VX18CJT	RAC-VX24CJT
Phase, Voltage, Frequency	Φ, V/Hz		1Φ, 50Hz, 220-230V		
Cooling Capacity	kW		3.4(0.9-4.2)	5.00(0.9-5.8)	6.2 (1.50-8.00)
	BTU/h		11,598(3,070-14,330)	18,603(3,070-19,791)	21,160 (5,118-27,304)
SEER	BTU/h ·W		19.55	21.05	≥ 20.0
Total Input	W		983(330-1,280)	1,510(320-2,000)	2,150(350-2,820)
Total Amperes	A		5.24-5.02	6.5	9.87-9.44
Air flow (Powerful/H/M/L/Silent)	m <sup>3</sup> /min		12.0/10.0/8.0/6.0/4.5	11.5/10.5/8.0/6.0	15.0/14.5/12.0/8.0/6.0
Indoor Sound Level (Powerful/H/M/L/Silent)	dB		48/44/35/27/19	44/42/37/32/19	49/48/40/33/30
Dehumidifying Capacity	l/h		1.6	3.4	4.5
Maximum Length/Height of Piping	m		20/10	20/10	30/20
Diameter for Gas / Liquid	mm		9.52/6.35	12.7/6.35	12.7/6.35
Power Supply			Indoor	Indoor	Indoor
Net Dimensions	Indoor (W × H × D)	mm	790×300×280	900×300×230	900×300×230
	Outdoor (W × H × D)	mm	750×570×280	850×650×298	850×750×298
Net Weight	Indoor/Outdoor	kg	11/32	10/47	10.5/47
Refrigerant			R32		

## Outdoor



RAC-VX13CJT



RAC-VX18CJT



RAC-VX24CJT

### Anti-Corrosion Green Fin

