

Standard Non-Inverter



Air Sleep Timer
STAINLESS PRE FILTER




RAS-S10CJT/ S13CJT



RAS-S18CJT



RAS-S10CJT/ S13CJT



RAS-S18CJT

Specification

Model	Indoor		RAS-S10CJT	RAS-S13CJT	RAS-S18CJT
	Outdoor		RAC-S10CJT	RAC-S13CJT	RAC-S18CJT
Phase, Voltage, Frequency	ΦV,Hz		1Φ,50Hz,220-230V		
Cooling Capacity	kW		2.8	3.6	5.5
	BTU/h		9,550	12,500	20,109
SEER	BTU/h ·W		13.4	12.28	13.43
Total Input	W		780	1,000	1,550
Total Amperes	A		3.60	4.64	7.1
Air flow (Powerful/H/M/L/Silent)	m3/min		13.5/11.5/8.5/7.0/5.0	12.0/11.5/9.0/7.5/6.2	19.0/16.0/13.5/11.5
Indoor Sound Level(Powerful/H/M/L/Silent)	dB		46/39/34/28/25	48/43/37/31/29	45/38/35/29
Dehumidifying Capacity	l/h		1.4	1.8	3.5
Maximum Length/Height of Piping	m		15/5	15/5	20/10
Diameter for Gas/Liquid	mm		9.52/6.35	12.7/6.35	12.7/6.35
Power Supply			Indoor	Indoor	Indoor
Net Dimensions	Indoor (W× H× D)	mm	790x300x230	790x300x230	1,100x300x250
	Outdoor (W× H× D)	mm	700x468x258	750x570x280	850x650x298
Net Weight	Indoor/Outdoor	kg	9.5/25	9.5/25.0	14.5/44
Refrigerant			R32		

Outdoor



RAC-S10CJT

RAC-S13CJT

RAC-S18CJT

- 1 ON Button
- 2 Powerful Mode 
- 3 Silent Mode 
- 4 Dry Mode 
- 5 Off Button
- 6 Air Sleep Timer
- 7 Fan Speed Selector
- 8 Set Temperature Selector
- 9 Off Timer Button
- 10 Up/Down Air Flow Control
- 11 On Timer Button
- 12 Left / Right Air Flow Control