

Product Specification

Model		HSU-10CQAB03T 1000 BTU	HSU-13CQAC03T 13000 BTU	HSU-18CQAB03T 18000 BTU	HSU-24CQAC03T 24000 BTU
Capacity (BTU/hr) (Min-Max)	Cooling	9200	12795	18000	24200
Power input (W)	Test from EGAT	760	1014	1450	2000
(Min-Max)	Cooling	No.5 no star	No.5 no star	No.5 no star	No.5 no star
Eneergy Star LevelNo.5		12.85	13	13.17	13.5
SEER		4.85	4.6	8.1	10.3
Running current (A)	Cooling	1/220/50	1/220/50	1/220/50	1/220/50
Power supply (Ph/V/Hz)		650	/	1100	/
Air circulation (m ³ /h)		1.6	/	2.0	/
Moisture removal (10 ⁻³ m ³ /h)		R32	R32	R32	R32
Refrigerant		6.35	6.35	6.35	6.35
Refrigerant pipe (mm)	Liquid side diameter	9.52	9.52	12.7	15.88
	Gas side diameter				
Indoor					
Net dimension (mm)	W/D/H	805*292*200	805/292/200	970*220*320	1106/240/345
Package dimension (mm)	W/D/H	874*363*270	874/363/270	1035*285*385	1166/310/410
Net weight (kg)		9.5	9.50	11.5	13.50
Gross weight (kg)		11.5	11.50	14.0	18.00
Noise [dB(A)] (Hi/Mid/Lo/So)		40/37/34/29	40/37/34/29	48/45/41/38	46/42/39/35
Outdoor					
Net dimension (mm)	W/D/H	700*245*544	800/275/553	800*280*550	890/340/705
Package dimension (mm)	W/D/H	845*320*590	954/409/625	954*409*625	1046/460/780
Net weight (kg)		25.0	33.00	34	56.20
Gross weight (kg)		26.8	36.00	37	62.50
Noise [dB(A)]		50	52	54	54



Remote Controller



Indoor Unit



Outdoor Unit