

Product Specification

Model		HSU-09VQAA03T1 9000BTU	HSU-12VQAA03T 12000BTU	HSU-15VQAA03T 15000BTU	HSU-18VQAA03T 18000BTU	HSU-24VQAA03T 24000BTU
Capacity (BTU/hr) (Min-Max)	Cooling	9200	12300	14700	18000	23200
Power input (W)	Test from EGAT	780	1160	1320	1760	1930
(Min-Max)	Cooling	No.5 no star	No.5 no star	No.5 no star	No.5 no star	No.5 no star
Energy Star Level	No.5	16	16	17.1	17.1	17.1
SEER		7.4	9.2	7.1	9.2	11.2
Running current (A)	Cooling	1/220/50	1/220/50	1/220/50	1/220/50	1/220/50
Power supply (Ph/V/Hz)		680	700	800	800	1100
Air circulation (m ³ /h)		1.2	1.6	1.8	2.0	2.0
Moisture removal (10 ⁻³ m ³ /h)		R32	R32	R32	R32	R32
Refrigerant		6.35	6.35	6.35	6.35	6.35
Refrigerant pipe (mm)	Liquid side diameter	9.52	9.52	9.52	12.7	12.7
	Gas side diameter					
Indoor						
Net dimension (mm)	W/D/H	805×200×292	805×200×292	875×217×307	875×217×307	975×220×318
Package dimension (mm)	W/D/H	876×365×272	876×365×272	945×390×296	945×390×296	1050×397×301
Net weight (kg)		8.4	8.4	11.5	12.0	11
Gross weight (kg)		10.5	10.5	13.8	13.5	13.5
Noise [dB(A)] (Hi/Mid/Lo/So)		40/37/33/29	40/37/33/29	46/42/38/32	46/42/38/32	48/45/41/38
Outdoor						
Net dimension (mm)	W/D/H	696×256×432	700×245×544	700×245×544	800×280×550	816×306×642
Package dimension (mm)	W/D/H	807×314×485	819×320×592	819×320×592	902×375×614	940×390×697
Net weight (kg)		18.5	20.6	24.0	29.7	40.0
Gross weight (kg)		22	23	26.0	32.5	44.0
Noise [dB(A)]		52	51	52	52	53



Remote Controller



Indoor Unit



Outdoor Unit